

## Table saw & Panel Safety and Operation Test

Name \_\_\_\_\_ Date \_\_\_\_\_

Multiple Choice - Write the letter that best answers the question to the left of the question number.

- \_\_\_\_\_ 1. If ripping a long board requires help, the helper must
- a. pull the board at the end of the cut
  - b. hold down the board
  - c. just support the board
  - d. pry the board apart
- \_\_\_\_\_ 2. Adjustments on the table saw are made
- a. while the saw is in motion
  - b. while the saw is coasting
  - c. when the blade is under the table
  - d. when the saw has stopped
- \_\_\_\_\_ 3. Dado-ing and tilting the arbor are special setups and must be
- a. checked by the instructor
  - b. checked by another student
  - c. done with care
  - d. done with special jigs
- \_\_\_\_\_ 4. When crosscutting stock, always use the
- a. rip fence
  - b. hold-down foot
  - c. sled or miter gauge
  - d. thickness gauge
- \_\_\_\_\_ 5. Before starting the table saw, you must
- a. have the teacher permission
  - b. remove the chuck key
  - c. ask the foreman
  - d. remove the guard
- \_\_\_\_\_ 6. A push stick must be used when ripping stock \_\_\_\_\_ or less.
- a. 3 inches wide
  - b. 5 inches wide
  - c. 1 inch wide
  - d. 6 inches wide
- \_\_\_\_\_ 7. Scraps may be cleared away from the saw only
- a. while it is moving
  - b. when it has stopped
  - c. when dado-ing
  - d. with a stick

